



IntelliFlash™

N-Series Storage Systems

- ▶ **NVMe-FLASH STORAGE OFFERS EXCEPTIONAL PERFORMANCE THAT CAN FUNDAMENTALLY TRANSFORM HOW YOU CONDUCT BUSINESS.**


But most flash-based solutions force you to compromise on performance, cost or enterprise capabilities.

The IntelliFlash N-Series is a fifth-generation intelligent storage infrastructure solution that doesn't require you to compromise. It delivers an exceptional user experience and outstanding cost-efficiency through automation, analytic insights, and a variety of time-saving management features to drive and optimize your most valuable workloads.

The N6000 Series is the latest addition to NVMe-based IntelliFlash offerings and leverages the industry's most mature NVMe platform. The IntelliFlash platform delivers unmatched innovation in flash management, data persistence, and data management, enabling the N6000 Series to deliver new levels of consolidation, simplicity, and economics.

Enterprises that need all-NVMe performance to accelerate their most demanding workloads can now access data faster than ever and with the lowest latencies to improve business insights and decision-making. Your enterprise workloads deserve uncompromised performance especially when they are key to your business success.

Customers have deployed the N-Series systems to accelerate high-performance databases, critical business applications, AI workloads, and large-scale virtualized servers. Exceptional performance at low latency, flexibility at scale, and comprehensive data services make IntelliFlash N-Series the choice for any performance-sensitive workload.



▶ FEATURES

- Synchronous Replication - Provides continuous business continuity and seamless data mobility between any IntelliFlash all-flash or hybrid systems located in different data centers
- Exceptional Performance - IntelliFlash N-Series confidently handles performance-sensitive workloads
- Cloud-Based Intelligent Analytics - Visibility across all IntelliFlash systems, with insights that keep infrastructure operating at peak efficiency and availability
- Unified Storage - Concurrent native block (FC, iSCSI) and file (NFSv3.x/v4.x, SMB1/2/3) access
- Comprehensive Data Services - Inline deduplication and compression, snapshots, read/write clones, and thin provisioning
- Live Dataset Migration - Seamless live migration of iSCSI/FC LUNs across IntelliFlash systems
- IntelliFlash S3 Cloud Connector - Hybrid cloud capabilities, enabling connectivity to the public cloud or any S3-compatible object storage
- VMware® Support - vCenter® plug-in and integration with VMware SRM and VAAI NAS
- Microsoft Hyper-V Support - PowerShell Toolkit plus SMB3 Enhancements for Hyper-V

▶ BENEFITS

- Maximizes Returns on Investment - Provide continuous availability and productivity for business-critical workloads
- Full Featured File Services - Enterprise grade NAS functionality for both virtualized and non-virtualized environments
- Simplified Management and Analytics - Common GUI management for all IntelliFlash systems
- Affordable Disaster Recovery - Replicate between any IntelliFlash systems
- Mixed Workload Consolidation - Support bare metal applications along with certified configurations for Oracle, Microsoft, VMware and many other environments
- Hybrid Cloud Flexibility - Back up local snapshots to the cloud or quickly migrate volumes for bring-up on any S3-compliant object storage
- Capacity as Needed - Without compromising on performance
- Reduced OPEX - With a platform that is energy efficient, offers inline data reduction, and is easy to maintain, so you can save on power, cooling, and labor

▶ INTELLIFLASH N-SERIES - NVMe-FLASH STORAGE SYSTEMS MODEL

MODELS	N6100	N6200
STORAGE CAPACITY		
NVMe FLASH CAPACITY (TB) †	46 to 184	46 to 368
NVMe EFFECTIVE CAPACITY (TB) ‡	Up to 920	Up to 1840
STORAGE CONTROLLERS	Dual Controller (active/active), fully redundant architecture	
ETHERNET DATA I/O PORTS	Up to 8x 40/100GbE, or 8x 10/25GbE	
FIBRE CHANNEL DATA I/O PORTS	Up to 8x 16 Gbps Fibre Channel	
NETWORK ADMIN PORTS	4x 10GbE, 2x 1GbE (IPMI)	
PHYSICAL SPECIFICATONS		
CONTROLLER FORM FACTOR	2RU with 24 NVMe SSD slots	
PHYSICAL DIMENSIONS (HxWxD)	3.4" x 17.6" x 33.5" (87.6mm x 446.4 mm x 850mm)	
WEIGHT (ESTIMATED)	80lbs (36.20kg) (chassis only) 91lbs (41.18kg) (fully populated with 24x SSDs)	
TYPICAL POWER USAGE (WATT)	800W (2730BTU/hr)	900W (3070BTU/hr)
ENVIRONMENTAL SPECIFICATIONS	Operating temperature: 10°C to 35°C (50°F ~ 95°F) Non-operating temperature: -40°C to 70°C (-40°F to 158°F) Operating relative humidity: 8% to 90% (non-condensing) Non-operating relative humidity: 5% to 95% (non-condensing)	
SOFTWARE SERVICES		
BLOCK AND FILE PROTOCOLS	SAN Protocols (iSCSI, Fibre Channel), NAS Protocols (NFS, SMB) Operating relative humidity: 20% to 90% (non-condensing)	
CAPABILITIES	IntelliFlash Operating Environment: Real-time deduplication and compression, snapshots and clones, space efficient thin provisioning, synchronous replication, full featured file services, S3 Cloud Connector, Live Dataset Migration, data-at-rest and data-in-flight encryption	
MANAGEMENT	IntelliFlash web UI, configuration wizard, Analytics for IntelliFlash, VMware plug-in for vCenter and support for vCenter Linked Mode, RBAC, SRA and VAAI NAS; Microsoft SCVMM/SMI-S, IP-KVM, SNMP, PowerShell Toolkit	
HARDWARE AVAILABILITY	Redundant storage controllers, fans, power supplies, and network ports; removable NVMe SSDs, SAS expansion	
WARRANTY		
BASIC	24x7 support via email and phone, next business day hardware replacement for defective parts, and software updates for the first 90 days	
OPTIONAL	Standard and Premier Service ddn.com/support/support-plans	

† Values indicated are RAW capacity. One MB is equal to one million bytes, one GB is equal to one billion bytes and one TB equals 1,000GB (one trillion bytes) when referring to storage capacity. Accessible capacity will vary from the stated capacity due to formatting and partitioning of the hard drives, the operating system and other factors.

‡ Effective capacity includes the benefit of data reduction with inline deduplication and compression. Data Reduction is calculated based on a 5:1 efficiency ratio. This efficiency ratio can vary based on workload type. Where a range is present, the values are Min - Max.

For more information on how DDN IntelliFlash systems can turbo-charge your business success with simplified Intelligent Infrastructure, visit www.ddn.com/intelliflash.